

# BALLISTIC SHIELDS

Data sheet TenCate Targa-Light™ CXP 800 TL

ADVANCED ARMOUR

## CXP-800 TL



<b>Configuration</b>	Anti-ballistic shield NIJ 0108.01, Level III & IV
<b>Type of protective cover</b>	Black textile or TenCate Rosist®
<b>Product application</b>	Handheld anti-ballistic shield
<b>Included Features</b>	Special aluminum handle Edge protection Velcro for accessories mounting

## SPECIAL THREATS TESTED

.30-06 APM2	
7.62 x 54 R API B32	
7.62 x 51 AP P80	
7.62 x 51 M80	
The above list of ammunition is not exhaustive and may not include threats that can be defeated by this product	



## SPECIFICATIONS

			
<b>Rifle ammo resistant</b>	<b>Multi-hit capability</b>	<b>Stop in plate capability</b>	<b>Lightweight</b>
.30-06 APM2 NIJ 0108.01, Level IV	3 shots NIJ 0108.01, Level IV	Against listed threats	17 kg ± 1 kg
			
<b>Dimensions</b>	<b>Shape</b>	<b>Composition</b>	<b>Durable</b>
500 x 900 mm ± 5 mm	Single curved	Ceramic HPPE	Sealed edges

› [www.tencateadvancedarmor.com](http://www.tencateadvancedarmor.com) › [advancedarmor@tencate.com](mailto:advancedarmor@tencate.com)  
 › DK: +45 6548 1600 › FR: +33 474 765 050 › UK: +44 1793 441 400  
 › SG: +65 6809 2100 › US: +1 740 928 0326

 TENCATE

#### AVAILABLE OPTIONS (Details on request)

- › Leg Protection
- › Camera (D/N, IR)
- › Lamp (LED, IR, Laser)
- › Transport (bag, straps, harness)

#### HANDLING

- › Keep away from intense heat source
- › Do not drop the shield on the floor and avoid hard shock(s)
- › Do a visual inspection of the shield every six-month
- › In case of visual damages, send the shield back for inspection / repair
- › Do only clean with pure water or mild soap
- › Use only as a shield, do not seat or walk on it

#### GUARANTEE PERIOD

The shield is expected to preserve its conformity with the specifications for a period of at least 5 years during storage from the date of delivery, provided that:

- › The product is stored under dry conditions at normal ambient temperature
- › The product has not been subjected to peak temperature exceeding 70°C
- › The product is protected against long term direct exposure to sun light