

Lightweight anti-ballistic shields

TenCate Targa-Light™ CX-501 TL

CX-501 TL

Product application	Tactical Anti-ballistic shield
Type of protective cover	Black Textile or TenCate Rosist®
Composition	<ul style="list-style-type: none"> • SiC ceramic & HPPE backing
Dimensions	<ul style="list-style-type: none"> • 450 x 800 mm ± 5mm
Weight	<ul style="list-style-type: none"> • Fabric : 12.5 Kg ± 1 Kg • TenCate Rosist® : 13.0 Kg ± 1 Kg
Shape	<ul style="list-style-type: none"> • Flat
Included features	<ul style="list-style-type: none"> • Aluminium handle, "no hole" fixing • Edge protection • Velcro for accessories mounting
Validity	<ul style="list-style-type: none"> • 11-10-2021



AVAILABLE OPTIONS

<ul style="list-style-type: none"> • Ballistic window. Vision 100 x 200 mm - 5 Kg 	<ul style="list-style-type: none"> • Leg Protection
<ul style="list-style-type: none"> • Transport (Bag, Strap, Harness) 	<ul style="list-style-type: none"> • IIIA : 410 x 460 mm - 1.7 Kg • III + MSC : 430 x 330 mm - 3.1 Kg
<ul style="list-style-type: none"> • Optronics (Lamps, Cameras...) 	
Details on request	

SPECIAL THREATS TESTED

Test temperature of 20°C
Multi hit (120 mm between shots)
<ul style="list-style-type: none"> • 5.56 x 45 SS109 (950 m/s ± 10 m/s) • 7.62 x 39 MSC (720 m/s ± 10 m/s) • 7.62 x 51 M80 (NIJ 0108.01, level III)
The above list of ammunition is not exhaustive and may not include threats that can be defeated by this product.

HANDLING

<ul style="list-style-type: none"> • Keep away from intense heat source
<ul style="list-style-type: none"> • Do not drop the shield on the floor and avoid hard shock(s)
<ul style="list-style-type: none"> • Do a visual inspection of the insert every six-month
<ul style="list-style-type: none"> • In case of visual damages, send the insert back for inspection / repair
<ul style="list-style-type: none"> • Do only clean with pure water or mild soap
<ul style="list-style-type: none"> • Use only as a shield, do not seat or walk on it

GUARANTEE PERIOD

The plate is expected to preserve its conformity with the specifications for a period of at least 5 years during storage from the date of delivery, provided that:

<ul style="list-style-type: none"> • The product is stored under dry conditions at normal ambient temperature
<ul style="list-style-type: none"> • The product has not been subjected to peak temperature exceeding 70°C
<ul style="list-style-type: none"> • The product is protected against long term direct exposure to sun light

Although TenCate Advanced Armour has used diligent care to ensure that the information provided in this document is accurate and up to date, TenCate Advanced Armour makes no representation or warranty, express or implied, as to the accuracy, reliability or complete-ness of the information. In no event shall TenCate Advanced Armour be liable for any damages arising from the reader's reliance upon, or use of, the information or materials contained in this document. The reader shall be solely responsible for any interpretation or use of this information and materials. The content of this document is subject to change without further notice. Please contact your TenCate Advanced Armour representative for more details.